



N NEENAH

digiscape® II wide format | 17 mil / 420 gsm C

FEATURES AND BENEFITS:

- Type II commercial Wall Decor
- Latex-saturated wet strength
- Laminated to PET backer
- Durable alternative to PVC
- Environmental and safety certificates
- Class "A" Fire Rating
- Low VOC

APPLICATIONS:

- Wall Decor
- Murals
- Paste application

PRINTABILITY:

- Eco-solvent / Solvent
- Latex
- UV
- Offset / Screen

DIGISCAPEII

800-558-5061 www.neenahpaper.com/wideformat

digiscape® II wide format | 17 mil / 420 gsm C

- DESCRIPTION:** PVC Free Eco-friendly digitally printable wallcovering, Type II 54", 36% post-consumer recycled content, for UV curable + Solvent + Eco Solvent + Latex inkjet printers
- CONSTRUCTION:** Proprietary Polyester/Natural Fiber Technology
- WEIGHT:** 12 ounces per 54" LY 8 ounces per SY 270 GSM
- AVAILABILITY:** Roll sizes: 54"x100ft, Trial Rolls (54"X20ft)
- PACKAGING:** 3" core, wound print side out, shipped in reusable cardboard tube
- APPLICATION:** Standard commercial wallcovering pastes/primers and techniques
- PHYSICALS:** TYPE II – Meets or exceeds federal specification CCCW-408D
- ENVIRONMENTAL:** PVC & POA (Olefin) Free, No Plasticizers, No Phthalates, No Formaldehyde, No Chlorine, No Halogen, No Heavy Metals, including: Cadmium, Mercury, Lead, or Zinc, and No Ozone Depleting Chemicals
- Minimum of 36% post-consumer recycled content
- Breathable – 47 Perms based on ASTM E96 Procedure B (wet cup)
- No harmful off gassing
- Low Voc emitting
- AIR QUALITY:** Meets California Section IAQ 1350 – Third party certified by Berkeley Analytical Associates
- FLAME AND SMOKE:** Class "A" Fire Rated – tested in accordance with ASTM-E84 Tunnel Test
- LEEDS ELIGIBILITY:** Digiscape® II can contribute towards the earning of up to 3 LEEDS credits
- MR Credit 4.1 Recycled content 10%
MR Credit 4.2 Recycled content 20%

Note: All LEED credits are based on the total construction of a building. Digiscape® II offers an advantage over competitive products for achieving MR credit 4.1 and MR Credit 4.2 because of its higher percentage of post consumer recycled materials

Conditionally

EQ Credit 4.1 When mounted with use of low emitting adhesives

- COMMENTS:** *Permeable surface allows transfer of moisture to minimize possibility of mold and mildew growth. Digiscape® II is intended for use in buildings that are properly designed and maintained to avoid moisture infiltration, condensation, and/or accumulation at wall cavities and wall surfaces, especially in warm, humid climates.