

## digiscape® installation instructions

### INSTALLATION GUIDELINES:

It is best to contact a professional paper hanger to perform proper installation for easy up and easy down wall covering or mural. A qualified installer can be found here: [http://www.ngpp.org/find\\_paperhanger.php](http://www.ngpp.org/find_paperhanger.php)

### Environment:

Room temperature should be above 65° F (18°C) for 48 hours prior to install.  
DigiScape® should be acclimated to the same temperature as installation point for 48 hours prior to install.  
Walls should not contain in excess of 5% residual moisture.

### SURFACE PREPARATION:

Hanging surface must be smooth, undamaged, and free of dirt and moisture.

### New Construction:

Use a white wall covering primer to conceal joints.  
Roman: PRO-977 ULTRA-PRIME® Premium Pigmented Primer or similar is recommended.

### Existing Construction:

Thoroughly clean surface of all dirt, grease, and anything that might adversely effect proper installation.  
Properly prime surface with suitable product.  
For painted drywall, Roman: PRO-909 VINYL PREP® Clear Wallpaper Primer or similar is recommended.  
When hanging on other surfaces use proper primer for the surface to be applied.

### PROCESS:

For new construction drywall and existing drywall installations use Strippable Wallcovering Adhesive or similar.  
Apply paste to wall with roller. For best results use a soft bristle brush working from the center of the panel out and smooth product on the wall.  
Use plastic strip or tape at seam to allow double cutting for a butt to butt installation.  
Clean any paste from DigiScape® surface with soft damp sponge.  
Apply paste for next panel. Line up panels at eye level and smooth from center out.  
Using proper primer and ample paste will allow DigiScape® to slide into alignment with previous panel.

### FINISHING:

When DigiScape® or any wall covering is to be hung in a high traffic area it is recommended to finish either pre-hanging or post-hanging with a clear coating.  
When finishing post-hanging Inx Digital ClearFlex™ ME can be applied with a paint roller following the manufacturers directions. This will ensure long life and greatly improve harm from abrasion.

### PRINTING TIPS:

Allow 2" bleed for top and bottom of total printed job.  
Allow 3/4 - 1 inch between panels.  
Print top to bottom to account for any differences in right to left printer color differences.

### FINISHING TIPS:

Leave product untrimmed as professional wall covering hanger can trim on site to ensure proper alignment.  
For high traffic areas a pressure (cold) laminating film or liquid coating can be applied.  
Adding this post installation will prevent any transit or damage that could occur during installation.  
Always be sure to make every new cut with a clean sharp blade tip to ensure precise edge trim.

These instruction are to be used as a guide for a successful installation of Neenah DigiScape® Wall Covering Product. Because there are a multitude of varying factors that are present in wall surfaces, and environments application testing is required before using product in production. Neenah will only warrant the product is manufactured to specification at the print service provider level. Any claims on manufacturing defect will be during print or finishing process.

