

# **N** classic<sup>®</sup> production inkjet

The best in class quality, performance and compatibility, designed specifically for your production inkjet presses. CLASSIC<sup>®</sup> Production Inkjet papers are guaranteed to be the papers to rely on for your digital inkjet needs.

## **Features**

## **Benefits**

Engineered for Production inkjet technology	Enhanced printability and reduced cost
Color Choice	Available in Solar White and Classic Natural White
Range of basis weights from 80T through 130DTC	Choice of weights including heavyweight covers
Available in multiple finishes	Options for Smooth, Linen, Laid and Techweave finishes
OEM approved	Approved compatibility with most major inkjet OEMs
Sheet and Roll options	Available in 13"x19"/19"x13", 23"x29"/29"x23" and 20" roll form
FSC <sup>®</sup> Certified options	Meets the mark of responsible forestry
Manufactured acid free with archival properties	Permanence

# N classic<sup>®</sup> production inkjet

## Paper Specifications - CLASSIC<sup>®</sup> Production Inkjet

Finish	Basis lbs.	Basis g/m <sup>2</sup>	Opacity	Caliper	Smoothness
Laid	100DTC	270	99	16	N/A
Linen	80T	118	95	5.6	N/A
	100C	270	99	13	N/A
Smooth	80T	118	96	5.8	125
	100C	270	99	12.5	125
	130DTC	352	99	16	125
Techweave	100C	270	99	15	N/A

- Opacity specifications are for whites and near whites.
- Caliper values are approximate as grades run to basis weight and finish.
- Smoothness is in Sheffield units.

## Special Make Minimums

### Standard Minimums

COLOR	BASIS WEIGHT (Standard Colors)	SIZE
15,000 lbs.	10,000 lbs.	5,000 lbs

- \* Special colors are subject to inquiry and mill acceptance.
- \* Laminated sheets using standard basis weights and colors require 10,000 lbs total minimum with a \$30.00 per cwt upcharge.

# classic<sup>®</sup> production inkjet

Basis/ Caliper	Size	Item #	M wt	Product Type	Shts/ Pack	Shts/ Ctn	Ctns/ Pallet
<b>Classic Natural White</b> FSC <sup>®</sup>							
FSC Mix Smooth							
100C / 12.5pt	19x13	<b>67774</b>	95	Sheet	125	500	30
100C / 12.5pt	23x29	<b>10080</b>	257	Sheet		300	28
<b>Solar White (97 Brightness)</b> FSC <sup>®</sup>							
FSC Mix Laid							
100DTC / 16pt	19x13	<b>10090</b>	95	Sheet	125	500	36
100DTC / 16pt	23x29	<b>10088</b>	257	Sheet		250	26
<b>Solar White (97 Brightness)</b> FSC <sup>®</sup>							
FSC Mix Linen							
80T / 5.6pt	13x19	<b>67771</b>	41.6	Sheet	250	1,000	30
80T / 5.6pt	29x23	<b>10076</b>	112	Sheet		750	26
100C / 13pt	19x13	<b>67772</b>	95	Sheet	125	500	30
100C / 13pt	20x12500	<b>67773</b>		Roll			
100C / 13pt	23x29	<b>10079</b>	257	Sheet		300	28
<b>Solar White (97 Brightness)</b> FSC <sup>®</sup>							
FSC Mix Smooth							
80T / 5.8pt	13x19	<b>67775</b>	41.6	Sheet	250	1,000	30
80T / 5.8pt	20x28000	<b>67776</b>		Roll			
80T / 5.8pt	29x23	<b>10081</b>	112	Sheet		750	24
100C / 12.5pt	19x13	<b>67777</b>	95	Sheet	125	500	30
100C / 12.5pt	20x13000	<b>67778</b>		Roll			
100C / 12.5pt	23x29	<b>10082</b>	257	Sheet		300	28
130DTC / 16pt	19x13	<b>67779</b>	123.5	Sheet	125	500	30
130DTC / 16pt	23x29	<b>10083</b>	334	Sheet		250	26
<b>Solar White (97 Brightness)</b> FSC <sup>®</sup>							
FSC Mix Techweave							
100C / 15pt	19x13	<b>67780</b>	95	Sheet	125	500	30
100C / 15pt	20x10800	<b>67781</b>		Roll			
100C / 15pt	23x29	<b>10084</b>	257	Sheet		250	28

Key FSC<sup>®</sup> – FSC<sup>®</sup> Certified  – Renewable Electricity  – Green Seal Certified PCF – Processed Chlorine Free  
 – Minimum 30% Post Consumer DC – Duplex Cover DTC – Double Thick Cover SP – Skid Packed  
 WS – Wet Strength BR – Vellum Bristol IND – Index \* – Unwatermarked

