

N classic[®] production inkjet

The best in class quality, performance and compatibility, designed specifically for your production Ink Jet presses. CLASSIC[®] Production Inkjet papers are guaranteed to be the papers to rely on for your digital ink jet needs.

Features

Benefits

Engineered for Production InkJet technology	Enhanced printability and reduced cost
Color Choice	Available in Solar and Classic Natural White
Range of basis weights from 80T through 130DTC	Choice of weights including heavyweight covers
Available in multiple finishes	Options for Smooth, Linen and Techweave finishes
OEM approved	Profiles and settings are established for ease of use (Canon IX & Prostream.)
Sheet and Roll options	Available in 13x19/19x13 and 20" roll form
FSC [®] Certified options	Meets the mark of responsible forestry
Manufactured acid free with archival properties	Permanence

N classic[®] production inkjet

Paper Specifications - CLASSIC[®] Production Inkjet

Finish	Basis lbs.	Basis g/m ²	Opacity	Caliper	Smoothness
Linen	80T	118	95	5.6	N/A
	100C	270	99	13	N/A
Smooth	80T	118	96	5.8	125
	100C	270	99	12.5	125
	130DTC	352	99	16	125
Techweave	100C	270	99	15	N/A

- Opacity specifications are for whites and near whites.
- Caliper values are approximate as grades run to basis weight and finish.
- Smoothness is in Sheffield units.

Special Make Minimums

Standard Minimums

COLOR	BASIS WEIGHT (Standard Colors)	SIZE
15,000 lbs.	10,000 lbs.	5,000 lbs

- * Special colors are subject to inquiry and mill acceptance.
- * Laminated sheets using standard basis weights and colors require 10,000 lbs total minimum with a \$30.00 per cwt upcharge.

classic[®] production inkjet

Basis/ Caliper	Size	Item #	M wt	Product Type	Shts/ Pack	Shts/ Ctn	Ctns/ Pallet
Classic Natural White FSC [®]							
FSC Mix Smooth							
100C / 12.5pt	19x13	67774	95	Sheet	125	500	30
Solar White (97 Brightness) FSC [®]							
FSC Mix Linen							
80T / 5.6pt	13x19	67771	41.6	Sheet	250	1,000	30
100C / 13pt	19x13	67772	95	Sheet	125	500	30
100C / 13pt	20x12500	67773		Roll			
Solar White (97 Brightness) FSC [®]							
FSC Mix Smooth							
80T / 5.8pt	13x19	67775	41.6	Sheet	250	1,000	30
80T / 5.8pt	20x28000	67776		Roll			
100C / 12.5pt	19x13	67777	95	Sheet	125	500	30
100C / 12.5pt	20x13000	67778		Roll			
130DTC / 16pt	19x13	67779	123.5	Sheet	125	500	30
Solar White (97 Brightness) FSC [®]							
FSC Mix Techweave							
100C / 15pt	19x13	67780	95	Sheet	125	500	30
100C / 15pt	20x10800	67781		Roll			

Key FSC[®] – FSC[®] Certified  – Renewable Electricity  – Green Seal Certified PCF – Processed Chlorine Free
 – Minimum 30% Post Consumer DC – Duplex Cover DTC – Double Thick Cover SP – Skid Packed
 WS – Wet Strength BR – Vellum Bristol IND – Index * – Unwatermarked

