

N go-to digital™ papers

VERSATILE. ECONOMICAL. APPROVED.

Features

Benefits

Bright White color	Excellent white color for accurate and vivid colors.
Super Smooth finish	Excellent formation and uniform smooth surface offers incredible print performance.
Vellum Finish	A texture that adds a slight tactile feel, excellent for cards and other personalized items.
FSC certified	Meets the mark of responsible forestry
Digital platform	Our Universal digital finish is compatible with all digital presses. For guarantee & certifications details visit neenahpaper.com/digital
HP Indigo certified	Certified by HP Indigo
Manufactured acid free with archival properties	Permanence

N go-to digital™ papers

Paper Specifications - GO-TO DIGITAL™ papers

Finish	Basis lbs.	Basis g/m ²	Opacity	Caliper	Smoothness
Super Smooth	60T	89	91	3.7	70
	70T	104	93	4.3	70
	80T	118	96	4.9	70
	100T	148	97	6	70
	80C	216	98	9.1	100
	100C	270	98	12.1	100
	120C	324	98	14.2	100
Vellum Digital	100C	270	98	15	320

- Opacity specifications are for whites and near whites.
- Caliper values are approximate as grades run to basis weight and finish.
- Smoothness is in Sheffield units.

Special Make Minimums

Standard Minimums

COLOR	BASIS WEIGHT (Standard Colors)	SIZE
40,000 lbs.	10,000 lbs.	5,000 lbs.

- * Special colors are subject to inquiry and mill acceptance.
- * Laminated sheets using standard basis weights and colors require 10,000 lbs total minimum with a \$30.00 per cwt upcharge.

go-to digital™ papers

Basis/ Caliper	Size	Item #	M wt	Product Type	Shts/ Pack	Shts/ Ctn	Ctns/ Pallet
Bright White (98 Brightness) FSC®							
FSC Mix Super Smooth							
60T / 3.7pt	12x18	10022	27.28	Sheet	500	1,500	48
60T / 3.7pt	13x19	10023	31.2	Sheet	500	1,500	36
60T / 3.7pt	29.5x20.75	10024	77	Sheet		1,000	20
70T / 4.3pt	12x18	10025	31.82	Sheet	500	1,500	48
70T / 4.3pt	13x19	10026	36.4	Sheet	500	1,500	36
70T / 4.3pt	29.5x20.75	10027	90	Sheet		1,000	20
80T / 4.9pt	12x18	10016	36.36	Sheet	500	1,000	48
80T / 4.9pt	13x19	10001	41.6	Sheet	500	1,000	54
80T / 4.9pt	29.5x20.75	10014	103	Sheet		750	20
100T / 6pt	12x18	10017	45.46	Sheet	250	1,000	48
100T / 6pt	13x19	10002	52	Sheet	250	1,000	42
100T / 6pt	29.5x20.75	10013	129	Sheet		600	20
80C / 9.1pt	18x12	10018	66.46	Sheet	250	500	48
80C / 9.1pt	19x13	10003	76	Sheet	250	500	60
80C / 9.1pt	20.75x29.5	10012	188	Sheet		400	24
100C / 12.1pt	18x12	10019	83.06	Sheet	125	500	48
100C / 12.1pt	19x13	10004	95	Sheet	125	500	48
100C / 12.1pt	20.75x29.5	10011	235	Sheet		300	24
120C / 14.2pt	18x12	10020	99.68	Sheet	125	375	48
120C / 14.2pt	19x13	10005	114	Sheet	125	375	54
120C / 14.2pt	20.75x29.5	10010	283	Sheet		250	24
Bright White (98 Brightness) FSC®							
FSC Mix Vellum Digital							
100C / 15pt	18x12	10021	83.06	Sheet	125	500	48
100C / 15pt	19x13	10006	95	Sheet	125	500	42
100C / 15pt	20.75x29.5	10015	235	Sheet		250	24

Key **FSC®** – FSC® Certified  – Renewable Electricity  – Green Seal Certified **PCF** – Processed Chlorine Free
 – Minimum 30% Post Consumer **DC** – Duplex Cover **DTC** – Double Thick Cover **SP** – Skid Packed
WS – Wet Strength **BR** – Vellum Bristol **IND** – Index * – Unwatermarked

